

DRAINACE™ POLYETHYLENE PUMP CHAMBERS

Chamber model no.	DAP01/02	DAP05	DAP06/11/ 16/20	DAP07/10/ 14	DAP30	DAP50	DAP61
Capacity (L)	175/280	500	650/1125/ 1600/2075	650/1000/ 1450	3000	5000	6100
Steel mould-formed manufacture	✓	✓	✓	✓	✓	✓	✓
Nominal internal dimensions (mm)	710 x 710	Ø700	Ø1000	Ø1000	Ø1650	Ø1800	Ø1950
Internal depth/s (mm)	660/960	1400	1000/1600/ 2200/2800	1200/1700/ 2300	2050 ³	2400 ³	2300 ³
Max invert depth from surface (mm)	300/600	1000	500/1100/ 1700/2300	700/1200/ 1800	1550	1900	1800
Maximum discharge pipework size (mm)	50	50	80	80	80	100	100
Opening size (mm)	710 x 710	Ø560	600 x 600	Ø600	900 x 600	900 x 600	900 x 600
Cast iron or aluminium covers	✓	Plastic or cast iron	✓	Plastic or cast iron	Plastic or cast iron	Plastic or cast iron	Plastic or cast iron
Dual pump option	✗	✓	✓	✓	✓	✓	✓
Department of Health approved	✗	✗	✗	✓	✓	✓	✓

Please note: All measurements nominal and subject to change without notice.

Notes:

1. Chambers will need concrete ballast if installed in high ground water table area.
2. Load-bearing covers will need to be supported off surrounding concrete pavement or concrete backfill.