Description

The VA40 (HE) non-metallic double diaphragm pumps are excellent pumps for use in a wide range of applications across many industries. Those pumps are using the modern technology to make them the most effcient on the market! The air section is from Polypropylene, which makes the pump suitable to be installed in the most severe environments. The VA40 (HE) is available in 2 different materials for the pump body and 4 different materials available for the diaphragms. This makes it possible to select the best solution for your application.

Your benefits

- → Energy efficient
- → Less downtime
- → Easy to install, operate and maintain
- 🔺 Ant-ice muffler

- → Free of air lubrication
- → Non-stalling air valve
- → Can run-dry without damage
- ▲ Dry self-priming

Technical data				
Weight [kg]	Fluid & air section	PP	25,9	
		KP	33,6	
Max. suction lift [mwc]		Dry	4,9	
		Wet	9,4	
Temperature [°C]	Fluid section	Internals		
	Р	All except TF, TO	0	66
	Р	TF, TO	4	66
	К	VT,KY	0	107
	К	PP	0	66
	К	TF, TO	4	82
	К	SP	0	82
Max. Particle size [mm]			6,3	
Max. recommended viscosity (mPas)			15000	

Code VA40 No.1 No.2 No.3 No.4. No.5 No.6 No.7

No.1 Fluid section K = Kynar (PVDF) P = Polypropylene No.2 Air section

P = Polypropylene

No.3 Check valve seats KY = Kynar (PVDF) PP = Polypropylene SP = Santoprene SS = Stainless Steel

No. 4 Check valve balls

SP = Santoprene VT = Viton (FKM) TF = PTFE

No.5 Diaphragms SP = Santoprene

TF = PTFE/EPDM 2 piece TO = PTFE/EPDM overmolded VT = Viton (FKM)

No. 6 Connections

FC = Center Flange DIN/ANSI * FE = End Flange DIN/ANSI

No. 7 Options OO = Standard

* only available for VA40PP

EXAMPLE PUMP TYPE VA40PP PP TF TO FE OO

Verderair VA40 (HE) non-metallic













End flange models







1300 1 GLOBAL sales@globalpumps.com.au globalpumps.com.au

All dimensions are in mm. All dimensions are for guidance only.

Find your local supplier at www.verderair.com

For construction, installation and floor mounting drawings please contact your local authorised Verderair[®] distributor.

